



US 20230232158A1

(19) **United States**
(12) **Patent Application Publication** (10) **Pub. No.: US 2023/0232158 A1**
CHEN et al. (43) **Pub. Date: Jul. 20, 2023**

(54) **LOUDSPEAKER AND ELECTRONIC DEVICE**

H04R 9/02 (2006.01)
H04R 9/06 (2006.01)

(71) Applicant: **HUAWEI TECHNOLOGIES CO., LTD.**, SHENZHEN (CN)

(72) Inventors: **Wenguang CHEN**, Dongguan (CN);
Mingguang GUO, Dongguan (CN);
Ling TAO, Dongguan (CN)

(21) Appl. No.: **18/175,767**

(22) Filed: **Feb. 28, 2023**

Related U.S. Application Data

(63) Continuation of application No. PCT/CN2021/102268, filed on Jun. 25, 2021.

Foreign Application Priority Data

Sep. 1, 2020 (CN) 202010903510.5

Publication Classification

(51) **Int. Cl.**
H04R 9/04 (2006.01)
H04R 7/18 (2006.01)
H04R 7/12 (2006.01)
H04R 1/02 (2006.01)

(52) **U.S. Cl.**
CPC *H04R 9/043* (2013.01); *H04R 1/028* (2013.01); *H04R 7/12* (2013.01); *H04R 7/18* (2013.01); *H04R 9/06* (2013.01); *H04R 9/025* (2013.01); *H04R 9/045* (2013.01); *H04R 2400/11* (2013.01); *H04R 2499/15* (2013.01)

(57) **ABSTRACT**

This application relate to the field of electronic device technologies, and in particular, to a loudspeaker and an electronic device. Embodiments of this application are provided to resolve a technical problem of insufficient sensitivity of a loudspeaker caused by a small electromagnetic driving force that drives a voice coil to vibrate. According to a loudspeaker and an electronic device in embodiments of this application, a yoke includes a bottom part and a sleeve located on the side of the bottom part. An annular magnet is sleeved on the outer side of the sleeve. A voice coil is sleeved on the sleeve and located between the magnet and the sleeve. A damper is located in a region enclosed by the sleeve. An outer edge of the damper is connected to the voice coil, and a middle part of the damper is connected to the yoke.

