US 20240213807A1

(19) **United States**

(12) **Patent Application Publication**

(10) **Pub. No.: US 2024/0213807 A1**

(43) **Pub. Date: Jun. 27, 2024**

TOKUYAMA et al.

(54) **POWER TRANSMITTING DEVICE**

(71) Applicant: **TOYODA GOSEI CO., LTD.**, Kiyosu-shi (JP)

(72) Inventors: **Yuki TOKUYAMA**, Kiyosu-shi (JP); **Atsushi SUGIHARA**, Kiyosu-shi (JP); **Taku KOIKE**, Kiyosu-shi (JP); **Riho MAMIYA**, Nagoya-shi (JP); **Shinichiro FUKI**, Kiyosu-shi (JP)

(21) Appl. No.: **18/527,483**

(22) Filed: **Dec. 4, 2023**

(30) **Foreign Application Priority Data**

Dec. 21, 2022 (JP) 2022-204844

Publication Classification

(51) **Int. Cl.**

H02J 50/20 (2006.01)
B60Q 3/74 (2006.01)
B60R 16/03 (2006.01)
H02J 50/80 (2006.01)

(52) **U.S. Cl.**

CPC ***H02J 50/20*** (2016.02); ***B60Q 3/74*** (2017.02); ***B60R 16/03*** (2013.01); ***H02J 50/80*** (2016.02)

(57) **ABSTRACT**

A power transmitting device includes a power transmitting unit. The power transmitting unit is configured to transmit power through wireless power supply to a power receiving device disposed in a cabin of a mobile unit. At least one front seat and a rear seat are provided in the cabin to be aligned in a front-rear direction of the mobile unit. The interior of the cabin includes a first region that includes a region in which the front seat is disposed and a region on a front side, and a second region that includes a region in which the rear seat is disposed and a region on a rear side. The power transmitting unit is disposed such that a central axis of a power transmittable range in which the power can be transmitted is contained within the second region.