US 20220368153A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2022/0368153 A1**

HAKUSHIMA et al. (43) **Pub. Date: Nov. 17, 2022**

(54) **POWER SUPPLY CONTROL DEVICE AND POWER SUPPLY CONTROL METHOD**

(71) Applicant: **DENSO TEN Limited**, Kobe-shi (JP)

(72) Inventors: **Daiki HAKUSHIMA**, Kobe-shi (JP); **Takeshi MATSUMOTO**, Kobe-shi (JP)

(73) Assignee: **DENSO TEN Limited**, Kobe-shi (JP)

(21) Appl. No.: **17/479,134**

(22) Filed: **Sep. 20, 2021**

(30) **Foreign Application Priority Data**

May 17, 2021 (JP) 2021-083162

Publication Classification

(51) **Int. Cl.**

H02J 9/06 (2006.01)

H02J 7/00 (2006.01)

(52) **U.S. Cl.**

CPC ***H02J 9/061*** (2013.01); ***H02J 7/0031*** (2013.01); *B60R 16/033* (2013.01)

(57) **ABSTRACT**

A power supply control device includes a first system, a second system, an inter-system switch, a battery switch and a controller. The controller turns off an inter-system switch that connects and disconnects the systems and turns on a battery switch that connects and disconnects a second power supply to and from the second system in response to an abnormality of a first power supply or the second power supply being detected and thereafter turn on the inter-system switch and turns off the battery switch in response to determination that there is no abnormality in the power supplies. Before turning on the inter-system switch, when voltage difference between the power supplies is equal to or larger than a threshold, the controller performs convergence control, and after determining that there is no abnormality in the power supplies, the controller keeps the battery switch turned off while performing the convergence control.