

# (19) United States

# (12) Patent Application Publication (10) Pub. No.: US 2024/0179960 A1 KAWAMURA

### May 30, 2024 (43) **Pub. Date:**

### (54) DISPLAY DEVICE AND MANUFACTURING METHOD THEREOF

- (71) Applicant: Japan Display Inc., Tokyo (JP)
- (72) Inventor: Shinichi KAWAMURA, Tokyo (JP)
- (73) Assignee: Japan Display Inc., Tokyo (JP)
- (21) Appl. No.: 18/498,048
- (22) Filed: Oct. 31, 2023
- (30)Foreign Application Priority Data

Nov. 24, 2022 (JP) ...... 2022-187255

## **Publication Classification**

(51) Int. Cl. H10K 59/123 (2006.01)H10K 59/12 (2006.01)H10K 59/122 (2006.01)

U.S. Cl. CPC ...... H10K 59/123 (2023.02); H10K 59/1201 (2023.02); H10K 59/122 (2023.02)

#### (57)ABSTRACT

According to one embodiment, a display device includes a circuit layer, an insulating layer comprising a contact hole, a lower electrode provided above the insulating layer and connected to the pixel circuit through the contact hole, a filling material inside the contact hole, a rib including a pixel aperture, a partition above the rib, an organic layer covering the lower electrode, and an upper electrode covering the organic layer. The rib and the partition overlap an entire of the contact hole as seen in plan view. A thickness of the filling material is less than a depth of the contact hole.

