

## (19) United States

# (12) Patent Application Publication (10) Pub. No.: US 2024/0213950 A1

Fukuhara et al.

Jun. 27, 2024 (43) Pub. Date:

#### (54) ACOUSTIC WAVE DEVICE WITH MULTI-LAYER SUBSTRATE INCLUDING **CERAMIC**

(71) Applicant: Skyworks Solutions, Inc., Irvine, CA (US)

(72) Inventors: Hironori Fukuhara, Ibaraki-Shi (JP); Rei Goto, Osaka-Shi (JP); Keiichi

Maki, Suita-Shi (JP)

(21) Appl. No.: 18/526,616

(22) Filed: Dec. 1, 2023

### Related U.S. Application Data

- (63) Continuation of application No. 16/800,248, filed on Feb. 25, 2020, now Pat. No. 11,876,501.
- Provisional application No. 62/810,707, filed on Feb. 26, 2019, provisional application No. 62/810,649, filed on Feb. 26, 2019.

#### **Publication Classification**

(51) Int. Cl. H03H 9/02 (2006.01)H03H 3/10 (2006.01)

H03H 9/05	(2006.01)
H03H 9/145	(2006.01)
H03H 9/25	(2006.01)
H03H 9/64	(2006.01)
H03H 9/72	(2006.01)
H10N 30/072	(2006.01)

(52) U.S. Cl.

CPC ....... H03H 9/02574 (2013.01); H03H 3/10 (2013.01); H03H 9/02031 (2013.01); H03H 9/02559 (2013.01); H03H 9/02834 (2013.01); H03H 9/0585 (2013.01); H03H 9/14502 (2013.01); H03H 9/25 (2013.01); H03H 9/6406 (2013.01); H03H 9/725 (2013.01); H10N 30/072 (2023.02)

#### (57)ABSTRACT

An acoustic wave device is disclosed. The acoustic wave device includes a support layer, a ceramic layer positioned over the support layer, a piezoelectric layer positioned over the ceramic layer, and an interdigital transducer electrode positioned over the piezoelectric layer. The support layer has a higher thermal conductivity than the ceramic layer. The ceramic layer can be a polycrystalline spinel layer. The acoustic wave device can be a surface acoustic wave device configured to generate a surface acoustic wave.

