

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2023/0232422 A1

Jul. 20, 2023 (43) **Pub. Date:**

(54) METHOD AND DEVICE FOR REPORTING HARQ FEEDBACK TO BASE STATION IN NR V2X

(52) U.S. Cl. CPC H04W 72/232 (2023.01); H04W 72/1263 (2013.01); **H04L 1/1812** (2013.01)

(71) Applicant: LG Electronics Inc., Seoul (KR)

Seoul (KR)

(72) Inventors: Seungmin LEE, Seoul (KR); Daesung HWANG, Seoul (KR); Woosuk KO,

(57)ABSTRACT

(21) Appl. No.: 18/123,089

(22) Filed: Mar. 17, 2023

Related U.S. Application Data

- (63) Continuation of application No. 17/766,465, filed on Jan. 1, 1, filed as application No. PCT/KR2020/ 013464 on Oct. 5, 2020.
- (60) Provisional application No. 62/911,177, filed on Oct. 4, 2019.

Publication Classification

(51) Int. Cl. H04W 72/232 (2006.01)H04W 72/1263 (2006.01)H04L 1/1812 (2006.01) A method for a first device to perform wireless communication and a device supporting same. The method may include: receiving, from the base station through a second PDCCH, a second DCI including information related to a second SL resource and information related to a second PUCCH resource; transmitting a first physical sidelink shared channel (PSSCH) based on the first SL resource; and transmitting, to the base station through the second PUCCH resource, first hybrid automatic repeat request (HARQ) feedback information related to the first PSSCH and second HARQ feedback information related to the second PSSCH, based on a slot including the first PUCCH resource being same as a slot including the second PUCCH resource, wherein the second DCI is a last DCI among a plurality of DCIs including information related to the slot for PUCCH transmission.

receive MODE 1 grants from base station

S1410

transmit PSSCH and/or PSCCH to second device, based on MODE 1 grants

S1420

receive information on SL HARQ feedback for PSSCH and/or PSCCH from second device through PSFCH related to PSSCH and/or PSCCH

S1430

report information on SL HARQ feedback to base station by using PUCCH resource

S1440