



US 20240180002A1

(19) **United States**

(12) **Patent Application Publication**
ICHIKAWA

(10) **Pub. No.: US 2024/0180002 A1**

(43) **Pub. Date: May 30, 2024**

(54) **DISPLAY DEVICE, ELECTRONIC DEVICE,
AND METHOD OF MANUFACTURING
DISPLAY DEVICE**

Publication Classification

(51) **Int. Cl.**

H10K 59/80 (2006.01)

H10K 59/12 (2006.01)

H10K 59/35 (2006.01)

(52) **U.S. Cl.**

CPC **H10K 59/876** (2023.02); **H10K 59/1201**
(2023.02); **H10K 59/35** (2023.02)

(71) Applicant: **SONY SEMICONDUCTOR
SOLUTIONS CORPORATION,**
Kanagawa (JP)

(72) Inventor: **Tomoyoshi ICHIKAWA,** Kanagawa
(JP)

(73) Assignee: **SONY SEMICONDUCTOR
SOLUTIONS CORPORATION,**
Kanagawa (JP)

(21) Appl. No.: **18/551,644**

(22) PCT Filed: **Mar. 4, 2022**

(86) PCT No.: **PCT/JP2022/009435**

§ 371 (c)(1),

(2) Date: **Sep. 21, 2023**

(30) **Foreign Application Priority Data**

Mar. 31, 2021 (JP) 2021-061660

(57)

ABSTRACT

Provided are a display device and an electronic device in which a level difference between front sub-pixels can be suppressed even if a resonator structure is included, and a method of manufacturing the display device. A display device includes a plurality of sub-pixels corresponding to a plurality of color types, in which each of the sub-pixels includes a light emitting element including a first electrode, an organic layer, and a second electrode, and in at least the sub-pixels corresponding to one color type, a resonator structure that causes emitted light from the organic layer to resonate is formed and a refractive index adjustment layer is included in at least one of the first electrode or the second electrode.

