



US 20240251580A1

(19) **United States**

(12) **Patent Application Publication**  
**Kim et al.**

(10) **Pub. No.: US 2024/0251580 A1**

(43) **Pub. Date: Jul. 25, 2024**

(54) **LIGHT-EMITTING DEVICE AND  
ELECTRONIC APPARATUS INCLUDING  
THE SAME**

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-si  
(KR)

(72) Inventors: **Gyeongheon Kim**, Yongin-si (KR);  
**Sooryun Cho**, Yongin-si (KR); **Jihye**  
**Kim**, Yongin-si (KR); **Hollim Kim**,  
Yongin-si (KR); **Saerom Park**,  
Yongin-si (KR); **Yongsub Shim**,  
Yongin-si (KR); **Dongsun Yoo**,  
Yongin-si (KR)

(21) Appl. No.: **18/401,243**

(22) Filed: **Dec. 29, 2023**

(30) **Foreign Application Priority Data**

Dec. 30, 2022	(KR)	10-2022-0191106
Nov. 14, 2023	(KR)	10-2023-0157684
Dec. 28, 2023	(KR)	10-2023-0195517

**Publication Classification**

(51) **Int. Cl.**  
**H10K 50/11** (2006.01)  
**C09K 11/06** (2006.01)  
**H10K 85/30** (2006.01)  
**H10K 85/60** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **H10K 50/11** (2023.02); **C09K 11/06**  
(2013.01); **H10K 85/346** (2023.02); **H10K**  
**85/636** (2023.02); **H10K 85/656** (2023.02);  
**C09K 2211/185** (2013.01)

(57) **ABSTRACT**

A light-emitting device, an electronic apparatus including the light-emitting device, and a consumer product including the light-emitting device are provided. The light-emitting device includes a first electrode, a second electrode facing the first electrode, an interlayer arranged between the first electrode and the second electrode and including an emission layer, and a capping layer arranged outside the first electrode or outside the second electrode. The emission layer includes a first emitter, the first emitter emits first light having a maximum emission wavelength of 470 nm or less, the first emitter includes platinum (Pt), and the capping layer includes an amine compound.

10

