US 20240215443A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2024/0215443 A1**

YOSHIYASU et al. (43) **Pub. Date: Jun. 27, 2024**

(54) **ORGANIC COMPOUND AND LIGHT-EMITTING DEVICE**

(71) Applicant: **SEMICONDUCTOR ENERGY LABORATORY CO., LTD.**, Atsugi-shi (JP)

(72) Inventors: **Yui YOSHIYASU**, Atsugi (JP); **Nobuharu OHSAWA**, Zama (JP); **Hiromitsu KIDO**, Atsugi (JP); **Masatoshi TAKABATAKE**, Atsugi (JP); **Satoshi SEO**, Sagamihara (JP)

(21) Appl. No.: **18/525,103**

(22) Filed: **Nov. 30, 2023**

(30) **Foreign Application Priority Data**

Nov. 30, 2022 (JP) 2022-192372
Dec. 1, 2022 (JP) 2022-193138
Jan. 13, 2023 (JP) 2023-003459

Publication Classification

(51) **Int. Cl.**

H10K 85/60	(2006.01)
C07D 209/86	(2006.01)
C07F 7/08	(2006.01)
C09K 11/06	(2006.01)
H10K 85/40	(2006.01)

(52) **U.S. Cl.**

CPC ***H10K 85/6572*** (2023.02); ***C07D 209/86*** (2013.01); ***C07F 7/0812*** (2013.01); ***C09K 11/06*** (2013.01); ***H10K 85/40*** (2023.02); *H10K 50/11* (2023.02)

(57) **ABSTRACT**

A highly efficient and highly reliable light-emitting device is provided. The light-emitting device includes an organic compound layer between a pair of electrodes. The organic compound layer includes a light-emitting layer, the light-emitting layer includes a first organic compound, a second organic compound, and a light-emitting substance, the first organic compound contains deuterium, and in a PL measurement of a mixed layer of the first organic compound and the second organic compound, a spectrum of an exciplex is observed at room temperature, and a spectrum of the exciplex is not observed at a temperature in a temperature range of 4 K to 80 K, inclusive.