

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2022/0361339 A1

Nov. 10, 2022 (43) **Pub. Date:**

(54) SEMICONDUCTOR PACKAGE FOR IMPROVING POWER INTEGRITY **CHARACTERISTICS**

(71) Applicant: SAMSUNG ELECTRONICS CO., LTD., Suwon-si (KR)

(72) Inventors: Junghwa KIM, Seoul (KR); Junso PAK, Seongnam-si (KR); Heeseok

LEE, Suwon-si (KR); Moonseob JEONG, Seongnam-si (KR); Jisoo HWANG, Hwaseong-si (KR)

Appl. No.: 17/591,734

(22)Filed: Feb. 3, 2022

(30)Foreign Application Priority Data

May 6, 2021 (KR) 10-2021-0058788

Publication Classification

(51) Int. Cl. H05K 1/18 (2006.01)H01L 23/00 (2006.01)H01L 23/498 (2006.01)H05K 1/02 (2006.01) (52) U.S. Cl.

CPC H05K 1/181 (2013.01); H01L 24/16 (2013.01); H01L 23/49816 (2013.01); H01L 24/14 (2013.01); H05K 1/0228 (2013.01); H01L 2224/16225 (2013.01); H01L 2224/14135 (2013.01); H01L 2924/1205 (2013.01); H05K 2201/10734 (2013.01); H01L 25/0655 (2013.01)

(57)ABSTRACT

A semiconductor package including a circuit board including a first wiring region, a die mounting region surrounding the first wiring region, and a second wiring region surrounding the die mounting region; a plurality of wiring balls on the first wiring region and the second wiring region and spaced apart from one another, the plurality of wiring balls including a plurality of first wiring balls on the first wiring region and a plurality of second wiring balls on the second wiring region; a die on the die mounting region, the die including a plurality of unit chips spaced apart from one another, and a die-through region corresponding to the first wiring region and exposing the first wiring balls; and a plurality of die balls on the die and the die mounting region, the plurality of die balls being spaced apart from one another and electrically coupled to the circuit board.

10

