



US 20230232564A1

- (19) **United States**  
(12) **Patent Application Publication** (10) **Pub. No.: US 2023/0232564 A1**  
Yao et al. (43) **Pub. Date: Jul. 20, 2023**

(54) **MULTI-NODE SERVER, CABINET SERVER,  
AND BLADE SERVER**

*G06F 1/20*

(2006.01)

(71) Applicant: **Huawei Technologies Co., Ltd.**,  
Shenzhen (CN)

(52) **U.S. Cl.**

CPC ..... *H05K 7/1487* (2013.01); *G06F 1/20*  
(2013.01); *G06F 1/187* (2013.01);  
*G06F 1/189* (2013.01)

(72) Inventors: **Yimin Yao**, Shenzhen (CN); **Yiwei Fan**,  
Shenzhen (CN); **Cheng Huang**,  
Shenzhen (CN)

(21) Appl. No.: **18/187,008**

(57)

**ABSTRACT**

(22) Filed: **Mar. 21, 2023**

**Related U.S. Application Data**

(63) Continuation of application No. PCT/CN2021/  
117848, filed on Sep. 11, 2021.

(30) **Foreign Application Priority Data**

Sep. 24, 2020 (CN) ..... 202011019515.8

**Publication Classification**

(51) **Int. Cl.**  
*H05K 7/14* (2006.01)  
*G06F 1/18* (2006.01)

A multi-node server includes a plurality of nodes and a hard disk backplane. Each node includes a power supply module. The power supply module is built in the node. The hard disk backplane is connected to the plurality of nodes through a first connector. The power supply module of each node is connected to a power supply interface of another node through a second connector, where the first connector and the second connector are spaced apart, and air flowing from an air inlet of the multi-node server circulates through a spacing between the first connector and the second connector. A system backplane for connection is not arranged in the multi-node server, but is replaced with the first connector and the second connector with a relatively small volume.

