



US 20240213437A1

(54) **HIGH SOLID CONTENT BATTERY INK FOR PRINTED BATTERIES AND METHODS OF MAKING**

(71) Applicant: **Northeastern University**, Boston, MA (US)

(72) Inventors: **Hongli Zhu**, Arlington, MA (US); **Ying Wang**, Boston, MA (US)

(21) Appl. No.: **18/545,285**

(22) Filed: **Dec. 19, 2023**

Related U.S. Application Data

(60) Provisional application No. 63/434,715, filed on Dec. 22, 2022.

Publication Classification

(51) **Int. Cl.**
H01M 4/04 (2006.01)
H01M 4/505 (2006.01)

H01M 4/525 (2006.01)
H01M 4/62 (2006.01)
(52) **U.S. Cl.**
CPC **H01M 4/0414** (2013.01); **H01M 4/505** (2013.01); **H01M 4/525** (2013.01); **H01M 4/623** (2013.01); **H01M 4/625** (2013.01); **H01M 2220/20** (2013.01); **H01M 2220/30** (2013.01)

(57) **ABSTRACT**

A screen-printable electrode battery ink is described comprising a slurry of an active ingredient, conductive additive, a binder, and a solvent, the slurry having a solids content from about 40% by weight to about 70% by weight that is uniformly distributed in the solvent, wherein the ink has a thixotropic recovery rate from about 30 seconds to about 90 seconds, and wherein the binder has untwisted molecular chains. Methods for making the screen-printable electrode battery ink are also described. The screen-printable electrode battery inks can be used to screen print electrodes, for use in fast-charging battery. Fast-charging batteries can be incorporated into electronic devices, such as electric vehicles.

