US 20240214010A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2024/0214010 A1**

Sittler et al. (43) **Pub. Date: Jun. 27, 2024**

(54) **METHOD FOR DEMODULATING A RF SIGNAL**

(71) Applicant: **STMicroelectronics (Grand Ouest) SAS**, Le Mans (FR)

(72) Inventors: **Francois Sittler**, Thorigne-Fouillard (FR); **Patrick Guyard**, Noyal sur Vilaine (FR)

(21) Appl. No.: **18/392,372**

(22) Filed: **Dec. 21, 2023**

(30) **Foreign Application Priority Data**

Dec. 22, 2022 (EP) 22306990.7

Publication Classification

(51) **Int. Cl.**
H04B 1/00 (2006.01)
H04B 1/16 (2006.01)

(52) **U.S. Cl.**
CPC ***H04B 1/0096*** (2013.01); ***H04B 1/0014*** (2013.01); ***H04B 1/1607*** (2013.01)

(57) **ABSTRACT**

The present disclosure relates to a method for demodulating a RF signal comprising the steps of: detecting if an analog to digital converter (ADC) of a Near Zero Intermediate Frequency (NZIF) receiver is in a clipping state; and if yes: determining and storing a first value (RSSI1) representative of the energy of a received signal demodulated by the Near Zero Intermediate Frequency (NZIF) receiver using a first intermediate frequency (IF1); determining and storing a second value (RSSI2) representative of the energy of the received signal demodulated by the Near Zero Intermediate Frequency (NZIF) receiver using a second intermediate frequency (IF2) corresponding to the opposite value of the first intermediate frequency (IF1), selecting the intermediate frequency corresponding to the lowest value of said first and second values.