



US 20240214279A1

(19) **United States**

(12) **Patent Application Publication**

ADILETTA et al.

(10) **Pub. No.: US 2024/0214279 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **MULTI-NODE SERVICE RESILIENCY**

(52) **U.S. Cl.**
CPC **H04L 41/5019** (2013.01); **H04L 41/16** (2013.01); **H04L 43/0823** (2013.01)

(71) Applicant: **Intel Corporation**, Santa Clara, CA (US)

(72) Inventors: **Matthew J. ADILETTA**, Bolton, MA (US); **Zane BALL**, Portland, OR (US); **Susanne M. BALLE**, Hudson, NH (US); **Patrick CONNOR**, Beaverton, OR (US)

(57) **ABSTRACT**

(21) Appl. No.: **18/433,291**

(22) Filed: **Feb. 5, 2024**

Publication Classification

(51) **Int. Cl.**
H04L 41/5019 (2022.01)
H04L 41/16 (2022.01)
H04L 43/0823 (2022.01)

Examples described herein relate to determining whether to process or not process data based on a reliability metric. For example, based on receiving a response to a request to a first microservice, with the reliability metric, from one or more servers, a decision can be made of whether to process, by a second microservice, a result associated with the response based on the reliability metric. In some examples, the reliability metric comprises an indicator of memory health and computational accuracy.

