



US 20220386470A1

(19) **United States**(12) **Patent Application Publication**
JEONG(10) **Pub. No.: US 2022/0386470 A1**(43) **Pub. Date: Dec. 1, 2022**(54) **DISPLAY DEVICE**(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-si
(KR)(72) Inventor: **JONGYUN JEONG**, Hwaseong-si
(KR)(21) Appl. No.: **17/670,848**(22) Filed: **Feb. 14, 2022**(30) **Foreign Application Priority Data**

May 25, 2021 (KR) 10-2021-0066963

Publication Classification(51) **Int. Cl.**

H05K 1/18	(2006.01)
H01L 25/16	(2006.01)
H01L 27/12	(2006.01)
H01L 27/32	(2006.01)
H01L 51/52	(2006.01)
H05K 1/14	(2006.01)

(52) **U.S. Cl.**CPC **H05K 1/189** (2013.01); **H01L 25/167**
(2013.01); **H01L 27/124** (2013.01); **H01L**
27/3276 (2013.01); **H01L 51/525** (2013.01);
H05K 1/147 (2013.01); **H05K 2201/10128**
(2013.01)

(57)

ABSTRACT

A display device may include a driving element substrate including a plurality of driving elements, a circuit board disposed on a first surface of the driving element substrate in a first direction, a cover substrate disposed to overlap the driving element substrate on a second surface of the driving element substrate in a second direction opposite to the first direction, where the cover substrate includes a protrusion protruding from the driving element substrate to an outside in a third direction intersecting to the first direction, and includes a connection line, a conductive spacer disposed between the driving element substrate and the cover substrate to electrically connect the driving element substrate and the cover substrate, and a circuit film including a first end connected to the protrusion of the cover substrate and a second end connected to the circuit board and opposite to the first end.

