



US 20230232162A1

(19) **United States**(12) **Patent Application Publication**
Yueh et al.(10) **Pub. No.: US 2023/0232162 A1**(43) **Pub. Date: Jul. 20, 2023**(54) **ELECTRONIC DEVICE****Publication Classification**(71) Applicant: **Innolux Corporation**, Miaoli County (TW)(72) Inventors: **Jui-Jen Yueh**, Miaoli County (TW);
Kuan-Feng Lee, Miaoli County (TW);
Tsung-Han Tsai, Miaoli County (TW);
Shun-Cheng Chen, Miaoli County (TW);
Ting-Wei Liang, Miaoli County (TW)(73) Assignee: **Innolux Corporation**, Miaoli County (TW)(21) Appl. No.: **18/085,553**(22) Filed: **Dec. 20, 2022**(30) **Foreign Application Priority Data**

Jan. 17, 2022 (CN) 202210051284.1

(51) **Int. Cl.****H04R 17/00** (2006.01)**H04R 1/34** (2006.01)**H04R 1/28** (2006.01)**H04R 1/02** (2006.01)(52) **U.S. Cl.**CPC **H04R 17/00** (2013.01); **H04R 1/345** (2013.01); **H04R 1/288** (2013.01); **H04R 1/028** (2013.01); **H04R 2499/15** (2013.01)

(57)

ABSTRACT

The disclosure provides an electronic device including a substrate, a first vibrating unit, and a supporting unit. The substrate has a first surface. The first vibrating unit is disposed on the first surface and has a second surface. The second surface faces the first surface. The supporting unit is disposed between the substrate and the first vibrating unit. The first surface and the second surface are separated by a distance through the supporting unit. This distance ranges from equal to or greater than 0.06 mm to equal to or less than 65.4 mm.

