



(10) Pub. No.: US 2024/0237434 A9
(48) Pub. Date: Jul. 11, 2024
CORRECTED PUBLICATION

Publication Classification

(51) **Int. Cl.**
H10K 59/131 (2006.01)
H10K 59/12 (2006.01)
H10K 59/122 (2006.01)
H10K 59/40 (2006.01)
H10K 59/80 (2006.01)

(52) **U.S. Cl.**
CPC *H10K 59/131* (2023.02); *H10K 59/1201*
(2023.02); *H10K 59/122* (2023.02); *H10K*
59/40 (2023.02); *H10K 59/873* (2023.02)

(57) **ABSTRACT**

In an organic EL display device, a frame region provided outside a display region is provided with a damming wall extending on an outer periphery of the display region and a second lead-out wiring line extending across the damming wall from the display region side to an outside of the frame region. The damming wall includes a bank portion having a projecting shape and provided, in a part in which the second lead-out wiring line extends, on both sides in a direction in which the second lead-out wiring line extends with respect to a top portion of the damming wall. The bank portion is lower than a top portion of a second damming wall and forms, between the bank portion and the top portion, a trap portion having a recessed shape.

(57) **ABSTRACT**

(57) **ABSTRACT**

(57) **ABSTRACT**

(57) **ABSTRACT**

(57) **ABSTRACT**

(57) **ABSTRACT**

