



US 20230231110A1

(19) **United States**(12) **Patent Application Publication**
HOU et al.(10) **Pub. No.: US 2023/0231110 A1**(43) **Pub. Date: Jul. 20, 2023**(54) **CARBON-COATED LITHIATED
SILICON-BASED ELECTROACTIVE
MATERIALS AND METHODS OF MAKING
THE SAME***H01M 10/0525* (2006.01)*H01M 4/62* (2006.01)*H01M 4/04* (2006.01)(52) **U.S. Cl.**CPC *H01M 4/366* (2013.01); *H01M 4/386*
(2013.01); *H01M 10/0525* (2013.01); *H01M*
4/625 (2013.01); *H01M 4/0471* (2013.01);
H01M 4/0416 (2013.01); *H01M 2004/027*
(2013.01)(71) Applicant: **GM GLOBAL TECHNOLOGY
OPERATIONS LLC**, Detroit, MI (US)(72) Inventors: **Mengyan HOU**, Shanghai (CN);
Haijing LIU, Shanghai (CN); **Xiaochao
QUE**, Shanghai (CN); **Meiyuan WU**,
Shanghai (CN)(73) Assignee: **GM GLOBAL TECHNOLOGY
OPERATIONS LLC**, Detroit, MI (US)(21) Appl. No.: **17/882,876**(22) Filed: **Aug. 8, 2022**(30) **Foreign Application Priority Data**

Jan. 14, 2022 (CN) 202210043878.8

Publication Classification(51) **Int. Cl.***H01M 4/36* (2006.01)*H01M 4/38* (2006.01)

(57)

ABSTRACT

Negative electrodes for electrochemical cells that cycle lithium ions are provided. The negative electrodes comprise electroactive material particles that exhibit a core-shell structure defining a core made of a lithiated silicon-based material and a shell surrounding the core that is a bi-layer structure including first and second carbon coating layers. An electrical conductivity of the first carbon coating layer is greater than that of the second carbon coating layer. A method of manufacturing a negative electrode material is provided in which a first carbon coating layer is formed on an outer surface of a silicon-based precursor particle. The silicon-based precursor particle is exposed to a lithium source to form a lithiated silicon-based particle having the first carbon coating layer. A second carbon coating layer is formed on the first carbon coating layer over the lithiated silicon-based particle to form an electroactive material particle.

