

# (19) United States

## (12) Patent Application Publication (10) Pub. No.: US 2023/0230780 A1 YUAN et al.

Jul. 20, 2023 (43) Pub. Date:

## (54) PASSIVE TRIGGERED-POWER ELECTRONIC TAP-CHANGER DEVICE AND CONTACT DEVICE

(71) Applicants: ELECTRIC POWER RESEARCH INSTITUTE. CHINA SOUTHERN POWER GRID, Guangzhou, Guangdong (CN); SHANGHAI **HUAMING POWER EQUIPMENT** CO., LTD., Shanghai (CN)

(72) Inventors: Yao YUAN, Guangzhou, Guangdong (CN); Yi XIAO, Shanghai (CN); Xi ZHANG, Guangzhou, Guangdong (CN); Qiang ZHU, Shanghai (CN); Zongming HE, Shanghai (CN); Shuaibing WANG, Guangzhou, Guangdong (CN); Lianwei BAO, Guangzhou, Guangdong (CN); Jiahui YANG, Guangzhou, Guangdong (CN); Wenhao LI, Guangzhou, Guangdong (CN); Linjie ZHAO, Guangzhou, Guangdong (CN); Ruihai LI, Guangzhou, Guangdong (CN)

(73) Assignees: ELECTRIC POWER RESEARCH INSTITUTE. CHINA SOUTHERN POWER GRID, Guangzhou, Guangdong (CN); SHANGHAI **HUAMING POWER EQUIPMENT** CO., LTD., Shanghai (CN)

18/010,228 (21) Appl. No.:

(22) PCT Filed: May 6, 2021 (86) PCT No.: PCT/CN2021/091943 § 371 (c)(1), (2) Date: Dec. 14, 2022

#### (30)Foreign Application Priority Data

Jun. 29, 2020 (CN) ...... 202010601233.2 Feb. 8, 2021 (CN) ...... 202110170877.5

### **Publication Classification**

(51) Int. Cl. H01H 9/00 (2006.01)H01H 19/12 (2006.01)

U.S. Cl. CPC ...... H01H 9/0016 (2013.01); H01H 9/0027 (2013.01); H01H 19/12 (2013.01)

#### (57)ABSTRACT

Disclosed are a passive triggered-power electronic tapchanger device and a contact device. The power electronic tap-changer device comprises: two taps, a main contact, two auxiliary contacts, two trigger contacts, an output terminal, two thyristors, and four voltage divider resistors, which can achieve the passive triggering of a power electronic switch by means of controlling the auxiliary contacts and the trigger contacts. Provided in the present invention is a contact device for the passive triggered-power electronic tapchanger, comprising: at least two stationary contacts, a main contact, two thyristor trigger contacts, two thyristor auxiliary contacts, and a drive shaft, wherein the main contact, the thyristor trigger contacts, and the thyristor auxiliary contacts are fixed to the drive shaft, the contact device can switch the power electronic switch to different stationary contacts by means of controlling the rotation of the drive shaft, and maintains the switching time sequence of passive triggering.

