US 20220352891A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2022/0352891 A1**

Kondou et al. (43) **Pub. Date: Nov. 3, 2022**

(54) **OPERATION PANEL**

(71) Applicant: **Marelli Corporation**, Saitama-city, Saitama (JP)

(72) Inventors: **Daisuke Kondou**, Saitama-city, Saitama (JP); **Yuuichi Fukumitsu**, Saitama-city, Saitama (JP); **Hideto Ujiie**, Saitama-city, Saitama (JP)

(21) Appl. No.: **17/619,017**

(22) PCT Filed: **Jul. 1, 2020**

(86) PCT No.: **PCT/JP2020/025848**

§ 371 (c)(1),
(2) Date: **Dec. 14, 2021**

(30) **Foreign Application Priority Data**

Sep. 19, 2019 (JP) 2019-170331

Publication Classification

(51) **Int. Cl.**
H03K 17/975 (2006.01)
B60K 37/06 (2006.01)

(52) **U.S. Cl.**
CPC ***H03K 17/975*** (2013.01); ***B60K 37/06*** (2013.01); *B60K 2370/143* (2019.05); *H03K 2217/965* (2013.01)

(57) **ABSTRACT**

An operation panel provided on a vehicle is provided with: a panel member exposed to an interior of a vehicle cabin of the vehicle; an operation part provided on the panel member; and a load sensor provided so as to face a back surface of the panel member, the a load sensor being configured to detect that the operation part has been operated based on a load caused by a displacement of the panel member, wherein the load sensor is provided at a position where the displacement of the panel member is greater than a displaced amount of the operation part when the operation part is operated, the panel member has a projected portion projecting out from the back surface such that a tip end portion faces the load sensor, and the projected portion is formed of divided projected portions, the divided projected portions being provided by being divided into a plurality of parts.