



US 20240244854A1

(19) **United States**

(12) **Patent Application Publication**
SUN et al.

(10) **Pub. No.: US 2024/0244854 A1**

(43) **Pub. Date: Jul. 18, 2024**

(54) **VISIBLE LIGHT COMMUNICATION
DEVICE, DISPLAY SUBSTRATE, DISPLAY
DEVICE AND MANUFACTURING METHOD
OF THE DISPLAY SUBSTRATE**

Publication Classification

(51) **Int. Cl.**
H10K 39/32 (2006.01)
H10K 30/80 (2006.01)
(52) **U.S. Cl.**
CPC **H10K 39/32** (2023.02); **H10K 30/80**
(2023.02)

(71) Applicant: **BOE Technology Group Co., Ltd.,**
Beijing (CN)

(72) Inventors: **Zhongyuan SUN**, Beijing (CN); **Weijie
WANG**, Beijing (CN); **Rui HUANG**,
Beijing (CN); **Renquan GU**, Beijing
(CN); **Yujie LIU**, Beijing (CN); **Biqi
LI**, Beijing (CN)

(21) Appl. No.: **17/926,963**

(22) PCT Filed: **Dec. 10, 2021**

(86) PCT No.: **PCT/CN2021/137037**

§ 371 (c)(1),

(2) Date: **Nov. 21, 2022**

(57) **ABSTRACT**

The present disclosure provides a visible light communication device, a display substrate, a display device, and a manufacturing method of the display substrate. The visible light communication device includes: a protrusion structure arranged on a base substrate and protruding toward a photosensitive side of the visible light communication device; a first electrode covering the protrusion structure; a visible light sensing layer arranged at a side of the first electrode away from the protrusion structure; and a second electrode arranged at a side of the visible light sensing layer away from the first electrode. A surface of each of the first electrode, the visible light sensing layer and the second electrode away from the base substrate is provided with a protrusion facing the photosensitive side of the visible light communication device due to the protrusion structure.

