

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2023/0231178 A1 Amatucci et al.

(43) **Pub. Date:**

Jul. 20, 2023

(54) ELECTROCHEMICAL CELL HAVING THIN METAL FOIL PACKAGING AND A METHOD FOR MAKING SAME

(71) Applicant: Rutgers, The State University of New Jersey, New Brunswick, NJ (US)

(72) Inventors: Glenn Amatucci, Peapack, NJ (US); Irene Plitz, Toms River, NJ (US); Linda Sung, Morris Plains, NJ (US); Anthony Ferrer, Red Lion, NJ (US)

Appl. No.: 18/125,550

(22) Filed: Mar. 23, 2023

Related U.S. Application Data

- (63) Continuation of application No. 15/769,270, filed on Apr. 18, 2018, filed as application No. PCT/US2016/ 059071 on Oct. 27, 2016.
- (60) Provisional application No. 62/249,590, filed on Nov. 2, 2015.

Publication Classification

(51)	Int. Cl.	
	H01M 10/0525	(2006.01)
	H01M 50/545	(2006.01)
	H01M 50/105	(2006.01)
	H01M 50/133	(2006.01)
	H01M 50/119	(2006.01)
	H01M 4/133	(2006.01)

H01M 4/38	(2006.01)
H01M 4/66	(2006.01)
H01M 10/058	(2006.01)

(52) U.S. Cl.

CPC H01M 10/0525 (2013.01); H01M 50/545 (2021.01); H01M 50/105 (2021.01); H01M 50/133 (2021.01); H01M 50/119 (2021.01); H01M 4/133 (2013.01); H01M 4/38 (2013.01); H01M 4/661 (2013.01); H01M 10/058 (2013.01); H01M 2220/20 (2013.01); H01M 10/0585 (2013.01)

(57)ABSTRACT

An electrochemical cell is provided comprising a thin metal foil packaging made from at least one sheet of metal foil and having a perimeter extending around at least a portion of the electrochemical cell, as well as an electrochemical cell stack contained within the thin metal foil packaging, and a metalto-metal welded seal around at least a portion of the perimeter of the thin metal foil packaging. The metal-to-metal welded seal is hermetic or nearly hermetic. Furthermore, the metal-to-metal welded seal is narrow, having a width of less than about 1 mm, and is less than about 5 mm away from the electrochemical cell stack. In some embodiments, the thin metal foil packaging functions not only as a hermetically or near hermetically sealed packaging, but also as either the negative or positive current collector, with one electrode of the cell bonded to the foil packaging. A method for making the foregoing electrochemical cell is also provided and involves using laser energy the metal-to-metal welded seal, wherein the laser energy is applied to the foil at high speed using a scanning laser.

