



(12) **Patent Application Publication**
Hsia et al.

(43) **Pub. Date:** **Jul. 20, 2023**

(52) **U.S. Cl.**
CPC *H01S 3/06733* (2013.01); *H01S 3/06716*
(2013.01); *H01S 3/06737* (2013.01); *H01S*
3/2308 (2013.01); *H01S 3/0675* (2013.01);
H01S 3/094019 (2013.01); *H01S 3/0941*
(2013.01); *H01S 3/1618* (2013.01); *H01S*
3/094053 (2013.01)

(72) Inventors: **Chungho Hsia**, Bellevue, WA (US);
Pai-Sheng Shen, Bellevue, WA (US)

(22) Filed: **Aug. 22, 2022**

Related U.S. Application Data

(63) Continuation-in-part of application No. 17/576,890, filed on Jan. 14, 2022, now Pat. No. 11,592,620.

Publication Classification

(51) **Int. Cl.**
H01S 3/067 (2006.01)
H01S 3/23 (2006.01)
H01S 3/094 (2006.01)
H01S 3/0941 (2006.01)
H01S 3/16 (2006.01)

(57) **ABSTRACT**

An all-fiber laser oscillator comprises a laser cavity, an amplification fiber, a plurality of diode lasers, and at least one side-pump signal-and-pump combiner (combiner). The combiner comprises a double-clad fiber (DCF) and four or more multimode fibers (MMFs). DCF comprises a first taper portion, whereas each of MMFs comprises a second taper portion fused around DCF. MMFs are configured to carry a portion of combined optical energy (COE) and to couple to DCF. The first taper portion can partially compensate a beam divergence created by the second taper portion, thereby increasing a coupling efficiency of COE coupled from MMFs to DCF with improved thermal performance. In a coupling portion, a refractive index difference between MMFs and DCF is configured to form a backward coupling barrier to suppress an optical energy in DCF from coupling into MMFs, thereby protecting the plurality of diode lasers from damage.

