



US 20240213500A1

(19) **United States**

(12) **Patent Application Publication**
HIRAO et al.

(10) **Pub. No.: US 2024/0213500 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **ELECTRICALLY CONDUCTIVE MEMBER,
ELECTROCHEMICAL CELL DEVICE,
MODULE, MODULE HOUSING DEVICE,
SLURRY, ELECTRICALLY CONDUCTIVE
MEMBER MANUFACTURING METHOD,
CONDUCTIVE MATERIAL, AND
CONDUCTIVE POWDER MATERIAL**

(71) Applicant: **KYOCERA Corporation**, Kyoto-shi,
Kyoto (JP)

(72) Inventors: **Kazuki HIRAO**, Kirishima-shi,
Kagoshima (JP); **Akihiro HARA**,
Kirishima-shi, Kagoshima (JP); **Atsuki
YAMAGUCHI**, Kirishima-shi,
Kagoshima (JP)

(21) Appl. No.: **18/554,984**

(22) PCT Filed: **Apr. 13, 2022**

(86) PCT No.: **PCT/JP2022/017724**

§ 371 (c)(1),

(2) Date: **Oct. 11, 2023**

(30) **Foreign Application Priority Data**

Apr. 13, 2021 (JP) 2021-067807

Publication Classification

(51) **Int. Cl.**

H01M 8/0217 (2016.01)

C09D 1/00 (2006.01)

C09D 5/24 (2006.01)

H01M 8/0228 (2016.01)

H01M 8/12 (2016.01)

(52) **U.S. Cl.**

CPC **H01M 8/0217** (2013.01); **C09D 1/00**

(2013.01); **C09D 5/24** (2013.01); **H01M**

8/0228 (2013.01); **H01M 2008/1293** (2013.01)

(57)

ABSTRACT

An electrically conductive member includes a base member and a coating layer. The base member contains chromium. The coating layer covers the base member. The coating layer contains a conductive oxide and a first oxide that is an oxide of a first element whose absolute values of first ionization energy and free energy of formation of an oxide are smaller than those of chromium.

