



(19) **United States**

(12) **Patent Application Publication**
SHIN et al.

(10) **Pub. No.: US 2024/0179959 A1**

(43) **Pub. Date:** **May 30, 2024**

(54) **DISPLAY DEVICE AND METHOD OF MANUFACTURING THE SAME**

(71) Applicant: **SAMSUNG DISPLAY CO., LTD.**,
Yongin-si (KR)

(72) Inventors: **Hyuneok SHIN**, Yongin-si (KR);
Dokeun SONG, Yongin-si (KR);
Joonyong PARK, Yongin-si (KR);
Sukyoung YANG, Yongin-si (KR)

H10K 59/131 (2006.01)

H10K 59/38 (2006.01)

H10K 71/20 (2006.01)

H10K 71/60 (2006.01)

(52) U.S. Cl.

CPC *H10K 59/123* (2023.02); *H10K 59/1201*
(2023.02); *H10K 59/131* (2023.02); *H10K*
59/38 (2023.02); *H10K 71/231* (2023.02);
H10K 71/60 (2023.02)

(21) Appl. No.: 18/229,548

(22) Filed: **Aug. 2, 2023**

(30) **Foreign Application Priority Data**

Nov. 25, 2022 (KR) 10-2022-0160726

Publication Classification

(51) **Int. Cl.**

H10K 59/123 (2006.01)

H10K 59/12 (2006.01)

(57) **ABSTRACT**

A display device includes a substrate including a display area and a peripheral area surrounding the display area, a thin-film transistor disposed on the display area of the substrate, and a pixel electrode disposed on the thin-film transistor and electrically connected to the thin-film transistor. The pixel electrode includes a lower layer including titanium nitride (TiN), an intermediate layer disposed on the lower layer and including an aluminum alloy, and an upper layer disposed on the intermediate layer and including titanium oxide.

