



US 20230232542A1

(19) **United States**

(12) **Patent Application Publication**
LIN

(10) **Pub. No.: US 2023/0232542 A1**

(43) **Pub. Date: Jul. 20, 2023**

(54) **ELECTRONIC DEVICE AND
MANUFACTURING METHOD THEREOF**

H01L 33/24 (2010.01)

H01L 33/00 (2010.01)

H01L 25/075 (2006.01)

(71) Applicant: **InnoLux Corporation**, Miao-Li County
(TW)

(52) **U.S. Cl.**

CPC **H05K 3/303** (2013.01); **H05K 1/181**

(2013.01); **H01L 33/24** (2013.01); **H01L**

33/005 (2013.01); **H01L 25/0753** (2013.01);

H05K 2201/10166 (2013.01); **H05K**

2201/10174 (2013.01); **H05K 2201/10106**

(2013.01)

(72) Inventor: **Chun-Hsien LIN**, Miao-Li County
(TW)

(73) Assignee: **InnoLux Corporation**, Miao-Li County
(TW)

(21) Appl. No.: **18/120,987**

(57)

ABSTRACT

(22) Filed: **Mar. 13, 2023**

Related U.S. Application Data

(63) Continuation of application No. 17/507,756, filed on
Oct. 21, 2021, now Pat. No. 11,627,666.

Foreign Application Priority Data

Oct. 29, 2020 (CN) 202011186128.3

Sep. 30, 2021 (CN) 202111164135.8

Publication Classification

(51) **Int. Cl.**

H05K 3/30 (2006.01)

H05K 1/18 (2006.01)

An electronic device is provided, the electronic device includes a driving substrate, the driving substrate includes a plurality of first grooves and a plurality of second grooves, the first grooves and the second grooves have different sizes, at least one first electronic component of the plurality of first electronic components is disposed in one of the plurality of first grooves, at least one second electronic component of the plurality of second electronic components is disposed in one of the plurality of second grooves, a maximum length passing through a center of a bottom surface of the at least one first electronic component is defined as L1, a bottom length of one side of at least one second groove among the second grooves is defined as L2, and the at least one first electronic component and the at least one second groove satisfy the condition of L1>L2.

