US 20230232421A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2023/0232421 A1**

Yi et al. (43) **Pub. Date: Jul. 20, 2023**

(54) **CONTROL CHANNEL REPETITION CONFIGURATION**

(71) Applicant: **Ofinno, LLC**, Reston, VA (US)

(72) Inventors: **Yunjung Yi**, Vienna, VA (US); **Esmael Hejazi Dinan**, McLean, VA (US); **Ali Cagatay Cirik**, Chantilly, VA (US); **Hua Zhou**, Vienna, VA (US); **Jonghyun Park**, Syosset, NY (US); **Hyoungsuk Jeon**, Centreville, VA (US)

(73) Assignee: **Ofinno, LLC**, Reston, VA (US)

(21) Appl. No.: **18/102,176**

(22) Filed: **Jan. 27, 2023**

Related U.S. Application Data

(63) Continuation of application No. PCT/US21/43286, filed on Jul. 27, 2021.

(60) Provisional application No. 63/057,699, filed on Jul. 28, 2020.

Publication Classification

(51) **Int. Cl.**

H04W 72/232	(2006.01)
H04L 1/08	(2006.01)
H04L 5/00	(2006.01)

(52) **U.S. Cl.**

CPC ***H04W 72/232*** (2023.01); ***H04L 1/08*** (2013.01); ***H04L 5/0053*** (2013.01); ***H04L 5/0091*** (2013.01); ***H04L 5/0044*** (2013.01)

(57) **ABSTRACT**

A wireless device receives configuration parameters indicating: a control resource set (coreset) configured with a first transmission configuration indicator (TCI) state and a second TCI state; and a bitmap comprising a plurality of bits. Each bit of the plurality of bits indicates one of the first TCI state or the second TCI state and is for a respective repetition of repetitions of a downlink control information (DCI). The wireless device receive, via a search space associated with the coreset, each of a plurality of repetitions of a first DCI using an associated TCI state indicated by a respective bit of the plurality of bits.