

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0213233 A1

Jun. 27, 2024 (43) **Pub. Date:**

(54) OPTOELECTRONIC DEVICE PACKAGE AND METHOD OF MANUFACTURING THE **SAME**

(71) Applicant: Advanced Semiconductor

Engineering, Inc., Kaohsiung (TW)

Inventor: Chi-Han CHEN, Taoyuan (TW) (72)

Assignee: Advanced Semiconductor

Engineering, Inc., Kaohsiung (TW)

Appl. No.: 18/434,703

(22) Filed: Feb. 6, 2024

Related U.S. Application Data

Continuation of application No. 17/319,948, filed on May 13, 2021, now Pat. No. 11,894,354.

Publication Classification

(51) Int. Cl.

H01L 25/16 (2006.01)H01L 21/48 (2006.01)H01L 21/56 (2006.01)

H01L 21/683 (2006.01)H01L 23/00 (2006.01)(2006.01)H01L 23/31 H01L 23/538 (2006.01)

U.S. Cl.

CPC H01L 25/167 (2013.01); H01L 21/4853 (2013.01); H01L 21/4857 (2013.01); H01L 21/565 (2013.01); H01L 21/568 (2013.01); H01L 21/6835 (2013.01); H01L 23/3128 (2013.01); *H01L* 23/5383 (2013.01); *H01L* 23/5386 (2013.01); H01L 23/5389 (2013.01); H01L 24/19 (2013.01); H01L 24/20 (2013.01); H01L 2221/68372 (2013.01); H01L 2224/214 (2013.01)

(57)ABSTRACT

An optoelectronic device package includes a first redistribution layer (RDL), a first electronic die disposed over the first RDL, wherein an active surface of the first electronic die faces the first RDL. The optoelectronic device package further includes a second electronic die disposed over the first RDL, and a photonic die disposed over and electrically connected to the second electronic die. An active surface of the second electronic die is opposite to the first RDL.

