



US 20220368192A1

(19) **United States**(12) **Patent Application Publication****Degorce-Dumas et al.**(10) **Pub. No.: US 2022/0368192 A1**(43) **Pub. Date: Nov. 17, 2022**

(54) **SUPPORT FOR A MOTOR AND HEATING,
VENTILATION AND/OR
AIR-CONDITIONING DEVICE FOR A
MOTOR VEHICLE**

Publication Classification(51) **Int. Cl.****H02K 5/24** (2006.01)**F04D 29/66** (2006.01)**F04D 25/06** (2006.01)**F04D 25/08** (2006.01)(52) **U.S. Cl.****CPC** **H02K 5/24** (2013.01); **F04D 29/663**(2013.01); **F04D 25/06** (2013.01); **F04D****25/08** (2013.01)

(71) Applicant: **Valeo Systemes Thermiques**, Le
Mesnil Saint-Denis (FR)

(72) Inventors: **Clara Degorce-Dumas**, Le Mesnil
Saint Denis (FR); **Clémence
Kwaczewski**, Le Mesnil Saint-Denis
(FR); **Stéphane De Souza**, Le Mesnil
Saint-Denis (FR); **Vincent Guilbot**, Le
Mesnil Saint-Denis (FR); **Saad
Bennouna**, Le Mesnil Saint-Denis (FR)

(73) Assignee: **Valeo Systemes Thermiques**, Le
Mesnil Saint-Denis (FR)

(21) Appl. No.: **17/623,357**

(22) PCT Filed: **Jun. 16, 2020**

(86) PCT No.: **PCT/FR2020/051031**

§ 371 (c)(1),

(2) Date: **Dec. 28, 2021**

(30) **Foreign Application Priority Data**

Jun. 28, 2019 (FR) FR1907099

(57) **ABSTRACT**

The motor support (16) comprises an inner ring (20) able to receive an element of the motor and an outer ring (22) able to be fastened to a housing, and a means (24) of decoupling between the two coaxial rings (20; 22) comprising a plurality of pads (46) of elastomer material that are interposed between the inner ring (20) and the outer ring (22). Each pad (46) is substantially "H"-shaped in form. The two arms (46int, 46ext; 461, 462) of the «H» are separated by a distance B. Each arm (46int, 46ext; 461, 462) has a width D measured in the radial direction. The web (46a) of the "H" has a width A measured in the orthoradial direction. The ratio A/B B is greater than or equal to 1.4, and the ratio A/D is greater than or equal to 2.

