

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2022/0352701 A1 KATO et al.

Nov. 3, 2022 (43) **Pub. Date:**

(54) METHOD OF MANUFACTURING WIRING

MEMBER-EQUIPPED ADHEREND AND WIRING MEMBER-EQUIPPED ADHEREND

(71) Applicants: AutoNetworks Technologies, Ltd., Mie (JP); Sumitomo Wiring Systems, Ltd., Mie (JP); SUMITOMO ELECTRIC INDUSTRIES, LTD., Osaka (JP)

(72) Inventors: Hirotaka KATO, Mie (JP); Hiroki HIRAI, Mie (JP); Makoto HIGASHIKOZONO, Mie (JP); Kosuke SONE, Mie (JP)

(73) Assignees: AutoNetworks Technologies, Ltd., Mie (JP); Sumitomo Wiring Systems, Ltd., Mie (JP); SUMITOMO ELECTRIC INDUSTRIES, LTD., Osaka (JP)

17/761,471 (21) Appl. No.:

(22) PCT Filed: Aug. 6, 2020

PCT/JP2020/030162 (86) PCT No.:

§ 371 (c)(1),

(2) Date: Mar. 17, 2022

(30)Foreign Application Priority Data

Sep. 30, 2019 (JP) 2019-178906

Publication Classification

(51) Int. Cl. H02G 3/30 (2006.01)H05B 6/10 (2006.01)H01B 7/40 (2006.01)

U.S. Cl. CPC H02G 3/30 (2013.01); H05B 6/104 (2013.01); H01B 7/40 (2013.01)

(57)**ABSTRACT**

A method of manufacturing a wiring member equippedadherend includes: a step (a) providing at least one heat generation body generating heat by induction heating between a wiring member including at least one wire-like transmission member and a fixation surface of an adherend; a step (b) providing a magnetic field generation source on a side of the adherend with respect to the wiring member; a step (c) generating a magnetic field fluctuating by the magnetic field generation source; a step (d) making the heat generation body generate heat by induction heating caused by the magnetic field fluctuating by the magnetic field generation source; and a step (e) fixing the wiring member to the fixation surface of the adherend by heat generation in the heat generation body.

