



US 20240222955A1

(19) **United States**

(12) **Patent Application Publication**
Riehl et al.

(10) **Pub. No.: US 2024/0222955 A1**

(43) **Pub. Date: Jul. 4, 2024**

(54) **GROUND FAULT CIRCUIT INTERRUPTER (GFCI) DEVICES, SYSTEMS, AND METHODS**

Publication Classification

(71) Applicant: **Schneider Electric USA, Inc.**,
Andover, MA (US)

(51) **Int. Cl.**

H02H 3/33 (2006.01)

H01H 83/14 (2006.01)

(52) **U.S. Cl.**

CPC **H02H 3/331** (2013.01); **H01H 83/144**
(2013.01)

(72) Inventors: **Kenneth Riehl**, North Liberty, IA (US);
Joseph Hall, Colorado Springs, CO (US); **Juan Ignacio Melecio**, North
Liberty, IA (US); **Jeremy D. Schroeder**, Cedar Rapids, IA (US);
Jacob B. Guelff, Cedar Rapids, IA (US)

(73) Assignee: **Schneider Electric USA, Inc.**, Boston,
MA (US)

(21) Appl. No.: **18/138,258**

(22) Filed: **Apr. 24, 2023**

Related U.S. Application Data

(63) Continuation of application No. 18/101,060, filed on
Jan. 24, 2023.

(60) Provisional application No. 63/436,436, filed on Dec.
30, 2022.

(57) **ABSTRACT**

A ground fault circuit interrupter (GFCI) can include a current transformer (CT) comprising a single core, a first winding wound around the single core, and a second winding wound around the single core. The GFCI can include a ground fault (GF) detection module operatively connected to the first winding to receive signals from the first winding and configured to determine whether a line-to-ground fault exists. The GFCI can also include a GN stimulus operatively connected to the second winding to provide a GN stimulus signal to the second winding. The GFCI can also include a grounded neutral (GN) detection module operatively connected to second winding and configured to receive signals from the second winding to determine whether a neutral-to-ground fault exists.

