

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2023/0231362 A1 JENTZSCH et al.

Jul. 20, 2023 (43) **Pub. Date:**

(54) SEMICONDUCTOR LASER WITH A HORIZONTAL LASER ELEMENT AND A VERTICAL LASER ELEMENT, LIDAR SYSTEM AND PRODUCTION METHOD

(71) Applicant: ams-OSRAM International GmbH,

Regensburg (DE)

Inventors: Bruno JENTZSCH, Regensburg (DE);

Hubert HALBRITTER, Dietfurt-Toeging (DE)

(73) Assignee: ams-OSRAM International GmbH,

Regensburg (DE)

17/926,876 (21) Appl. No.:

(22)PCT Filed: May 4, 2021

PCT/EP2021/061694 (86) PCT No.:

> § 371 (c)(1), (2) Date:

Nov. 21, 2022

(30)Foreign Application Priority Data

May 26, 2020 (DE) 10 2020 206 580.2

Publication Classification

(51) Int. Cl. H01S 5/10 (2006.01)H01S 5/42 (2006.01)

H01S 5/343	(2006.01)
H01S 5/183	(2006.01)
H01S 5/185	(2006.01)
H01S 5/02255	(2006.01)
H01S 5/026	(2006.01)

(52) U.S. Cl.

CPC H01S 5/1021 (2013.01); H01S 5/423 (2013.01); H01S 5/34326 (2013.01); H01S *5/3432* (2013.01); *H01S 5/18305* (2013.01); H01S 5/185 (2021.01); H01S 5/02255 (2021.01); **H01S 5/026** (2013.01); G01S 7/4814 (2013.01)

ABSTRACT (57)

A semiconductor laser includes a horizontal laser element including a first semiconductor layer arrangement having a first active zone for generating radiation. The horizontal laser element furthermore includes a first optical resonator extending in a direction parallel to a first main surface of the first semiconductor layer arrangement. Lateral boundaries of the first semiconductor layer arrangement run obliquely, such that electromagnetic radiation generated is reflectable in a direction of the first main surface of the first semiconductor layer arrangement. The semiconductor laser furthermore includes a vertical laser element having a second optical resonator extending in a direction perpendicular to the first main surface of the first semiconductor layer arrangement. The vertical laser element is arranged above the first semiconductor layer arrangement on the side of the first main surface in a beam path of electromagnetic radiation reflected at one of the lateral boundaries of the first semiconductor layer arrangement (112).

