



US 20240215294A1

(19) **United States**

(12) **Patent Application Publication**

MANAGAKI et al.

(10) **Pub. No.: US 2024/0215294 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **DISPLAY DEVICE AND METHOD OF MANUFACTURING THE SAME**

(71) Applicant: **Japan Display Inc.**, Tokyo (JP)

(72) Inventors: **Nobuto MANAGAKI**, Tokyo (JP); **Hayata AOKI**, Tokyo (JP)

(73) Assignee: **Japan Display Inc.**, Tokyo (JP)

(21) Appl. No.: **18/391,684**

(22) Filed: **Dec. 21, 2023**

(30) **Foreign Application Priority Data**  
Dec. 23, 2022 (JP) ..... 2022-206916

**Publication Classification**

(51) **Int. Cl.**  
**H10K 50/18** (2023.01)  
**H10K 59/35** (2023.01)

**H10K 71/10** (2023.01)  
**H10K 101/40** (2023.01)

(52) **U.S. Cl.**  
CPC ..... **H10K 50/181** (2023.02); **H10K 59/35** (2023.02); **H10K 71/10** (2023.02); **H10K 2101/40** (2023.02)

(57) **ABSTRACT**

According to one embodiment, a display device includes an anode, a cathode opposing the anode and an organic layer located between the anode and the cathode, and the organic layer includes a hole injection layer, a hole transport layer, an electron blocking layer, a light emitting layer, a hole blocking layer, an electron transport layer, and an electron injection layer, and at least one of the electron blocking layer and the hole blocking layer has a resistance of 10% or more and 30% or less in a thickness direction when a total resistance between the anode and the cathode is set to 100%.