

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0215275 A1 CHOI et al.

Jun. 27, 2024 (43) **Pub. Date:**

(54) PHOTOELECTRIC DEVICE, LIGHT ABSORPTION SENSOR, SENSOR-EMBEDDED DISPLAY PANEL, AND **ELECTRONIC DEVICE**

(71) Applicant: Samsung Electronics Co., Ltd.,

Suwon-si (KR)

(72) Inventors: Tae Jin CHOI, Suwon-si (KR); Hveong-Ju KIM, Suwon-si (KR);

Daiki MINAMI, Suwon-si (KR); Kyung Bae PARK, Suwon-si (KR); Feifei FANG, Suwon-si (KR); Sungyoung YUN, Suwon-si (KR); Jeoung In YI, Suwon-si (KR);

Younhee LIM, Suwon-si (KR); Hyerim

HONG, Suwon-si (KR)

(73) Assignee: Samsung Electronics Co., Ltd.,

Suwon-si (KR)

Appl. No.: 18/531,205

(22)Filed: Dec. 6, 2023

(30)Foreign Application Priority Data

Dec. 9, 2022 (KR) 10-2022-0171991

Publication Classification

(51) Int. Cl. H10K 30/20 (2006.01)H10K 39/00 (2006.01)H10K 85/40 (2006.01)H10K 85/60 (2006.01)

(52) U.S. Cl.

CPC H10K 30/20 (2023.02); H10K 39/601 (2023.02); H10K 85/40 (2023.02); H10K 85/621 (2023.02); H10K 85/654 (2023.02); H10K 85/6572 (2023.02); H10K 85/6576 (2023.02); H10K 85/658 (2023.02); H10K 2101/30 (2023.02)

ABSTRACT (57)

Provided are a photoelectric device, a light absorption sensor, a sensor-embedded display panel, and an electronic device. The photoelectric device includes a first electrode and a second electrode facing each other, and a light absorbing layer between the first electrode and the second electrode, wherein the light absorbing layer is configured to absorb light of a red wavelength spectrum, a green wavelength spectrum, a blue wavelength spectrum, an infrared wavelength spectrum, or any combination thereof, the light absorbing layer includes a p-type semiconductor and an n-type semiconductor, and the n-type semiconductor includes a compound represented by Chemical Formula 1. Details for Chemical Formula 1 are as described in the detailed description.





