



US 20240235272A1

(19) **United States**

(12) **Patent Application Publication**  
**Wadkar et al.**

(10) **Pub. No.: US 2024/0235272 A1**

(43) **Pub. Date: Jul. 11, 2024**

(54) **CROSS TALK AND INTERFERENCE  
MITIGATION IN DUAL WIRELESS POWER  
TRANSMITTER**

**H04B 5/79** (2006.01)

**H04L 27/04** (2006.01)

(52) **U.S. Cl.**

**CPC** ..... **H02J 50/40** (2016.02); **H02J 50/10**  
(2016.02); **H02J 50/80** (2016.02); **H04L 27/04**  
(2013.01); **H04B 5/79** (2024.01)

(71) Applicant: **NuCurrent, Inc.**, Chicago, IL (US)

(72) Inventors: **Unnati Wadkar**, Bangalore (IN); **Marc  
Backas**, Chicago, IL (US); **Pavel  
Shostak**, San Diego, CA (US); **Glenn  
Riese**, McHenry, IL (US)

(21) Appl. No.: **18/519,813**

(22) Filed: **Nov. 27, 2023**

**Related U.S. Application Data**

(63) Continuation of application No. 17/683,982, filed on  
Mar. 1, 2022, now Pat. No. 11,831,174.

**Publication Classification**

(51) **Int. Cl.**

**H02J 50/40** (2006.01)

**H02J 50/10** (2006.01)

**H02J 50/80** (2006.01)

(57) **ABSTRACT**

A dual wireless power transfer system includes an input power supply and a first wireless power transmission system receiving power at a first power input from the input power supply. The first wireless power transmission system includes a first transmitter antenna and a first driver for driving the first transmitter antenna for wireless power transmission and wireless receipt of data, wherein data wirelessly received at the first transmitter antenna at least partially feeds back onto the first power input. A second wireless power transmission system includes a second transmitter antenna and a second driver for driving the second transmitter antenna for wireless power transmission. A low voltage drop out receives power from the input power supply and provides power at a preselected lower voltage to the second wireless power transmission system, such that  $V_2$  is independent of data received at the first transmitter antenna.

