



US 20230232686A1

(19) **United States**

(12) **Patent Application Publication**
CHO et al.

(10) **Pub. No.: US 2023/0232686 A1**

(43) **Pub. Date: Jul. 20, 2023**

(54) **DISPLAY APPARATUS**

H10K 59/40 (2006.01)

H10K 59/122 (2006.01)

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-si (KR)

(52) **U.S. CL.**

CPC **H10K 59/131** (2023.02); **H10K 50/844** (2023.02); **H10K 59/40** (2023.02); **H10K 59/122** (2023.02); **G09G 2300/0804** (2013.01); **G09G 2300/0408** (2013.01); **H01L 27/14678** (2013.01)

(72) Inventors: **Young Jin CHO**, Seoul (KR);
Joong-Soo MOON, Hwaseong-si (KR);
Yang Wan KIM, Hwaseong-si (KR);
Soon Jung WANG, Cheonan-si (KR)

(21) Appl. No.: **18/190,928**

(57)

ABSTRACT

(22) Filed: **Mar. 27, 2023**

Related U.S. Application Data

(63) Continuation of application No. 16/952,001, filed on Nov. 18, 2020, now Pat. No. 11,616,112.

Foreign Application Priority Data

Nov. 22, 2019 (KR) 10-2019-0151695

Publication Classification

(51) **Int. Cl.**

H10K 59/131 (2006.01)

H10K 50/844 (2006.01)

A display apparatus includes: a base substrate including a display area and a non-display area adjacent to the display area; a first power supply wire in the non-display area, a first power supply voltage being applied to the first power supply wire; a second power supply wire in the non-display area and spaced apart from the first power supply wire, a second power supply voltage being applied to the second power supply wire; and a dam overlapping the first power supply wire and the second power supply wire, having a first height on the first power supply wire, and having a second height greater than the first height between the first power supply wire and the second power supply wire.

