



(19) **United States**

(12) **Patent Application Publication**

Shah et al.

(10) **Pub. No.: US 2023/0231669 A1**

(43) **Pub. Date: Jul. 20, 2023**

(54) **NON-LEGACY PREAMBLE FOR WIRELESS LOCAL AREA NETWORKS**

application No. 61/645,948, filed on May 11, 2012.

(71) Applicant: **InterDigital Patent Holdings, Inc.**,
Wilmington, DE (US)

Publication Classification

(72) Inventors: **Nirav B. Shah**, San Diego, CA (US);
Sudheer A. Grandhi, Pleasanton, CA (US); **Ronald G. Murias**, Calgary, CA (US); **Guodong Zhang**, Woodbury, NY (US); **Xiaofei Wang**, North Caldwell, NJ (US); **Monisha Ghosh**, Chicago, IL (US); **Hanqing Lou**, Syosset, NY (US); **Robert L. Olesen**, Huntington, NY (US)

(51) **Int. Cl.**
H04L 5/00 (2006.01)
H04L 1/00 (2006.01)
(52) **U.S. Cl.**
CPC *H04L 5/0023* (2013.01); *H04L 1/0025* (2013.01); *H04L 1/0041* (2013.01); *H04L 1/0059* (2013.01); *H04L 1/0061* (2013.01); *H04L 5/0048* (2013.01); *H04L 5/0053* (2013.01); *H04L 25/0226* (2013.01)

(21) Appl. No.: **18/186,632**

(57) **ABSTRACT**

(22) Filed: **Mar. 20, 2023**

Related U.S. Application Data

(63) Continuation of application No. 16/213,633, filed on Dec. 7, 2018, now Pat. No. 11,611,414, which is a continuation of application No. 13/530,576, filed on Jun. 22, 2012, now abandoned.

(60) Provisional application No. 61/500,930, filed on Jun. 24, 2011, provisional application No. 61/586,525, filed on Jan. 13, 2012, provisional application No. 61/607,345, filed on Mar. 6, 2012, provisional

Method and apparatus for transmission and reception of a Greenfield preamble are provided. In the method and apparatus, the Greenfield preamble may be a single user (SU) preamble or a multi user (MU) preamble. As an MU preamble, the Greenfield preamble includes a short training field (STF), a first long training field (LTF), a first signal (SIG) field, at least one additional LTF, and a second SIG field. Additionally, the Greenfield preamble may be utilized for efficient transmission and reception of control information to wireless devices, whereby the control information may be indicated using the STF, the first LTF, or the first or second SIG fields.

