



US 20230231755A1

(19) **United States**

(12) **Patent Application Publication**  
**STADELMEIER et al.**

(10) **Pub. No.: US 2023/0231755 A1**

(43) **Pub. Date: Jul. 20, 2023**

(54) **RECEPTION METHODS AND APPARATUSES  
FOR NON-UNIFORM CONSTELLATION  
MODULATED SIGNALS**

(71) Applicant: **SATURN LICENSING LLC**, New  
York, NY (US)

(72) Inventors: **Lothar STADELMEIER**, Stuttgart  
(DE); **Jan ZOELLNER**, Braunschweig  
(DE); **Nabil LOGHIN**, Freiburg (DE)

(21) Appl. No.: **17/989,023**

(22) Filed: **Nov. 17, 2022**

**Related U.S. Application Data**

(63) Continuation of application No. 16/844,844, filed on  
Apr. 9, 2020, now Pat. No. 11,522,746, which is a  
continuation of application No. 16/020,554, filed on  
Jun. 27, 2018, now Pat. No. 10,659,275, which is a  
continuation of application No. 15/438,566, filed on  
Feb. 21, 2017, now Pat. No. 10,033,567, which is a  
continuation of application No. 14/412,265, filed on  
Dec. 31, 2014, now abandoned, filed as application  
No. PCT/EP2013/063824 on Jul. 1, 2013.

(30) **Foreign Application Priority Data**

Jul. 9, 2012 (EP) ..... 12175587.0  
Apr. 17, 2013 (EP) ..... 13164169.8

**Publication Classification**

(51) **Int. Cl.**  
**H04L 27/34** (2006.01)  
**H04L 1/00** (2006.01)  
**H03M 13/25** (2006.01)  
**H03M 13/35** (2006.01)  
**H04L 27/00** (2006.01)  
**H04L 27/38** (2006.01)  
**H04L 27/36** (2006.01)  
(52) **U.S. Cl.**  
CPC ..... **H04L 27/34** (2013.01); **H04L 1/0041**  
(2013.01); **H03M 13/25** (2013.01); **H03M**  
**13/356** (2013.01); **H04L 1/007** (2013.01);  
**H04L 1/0071** (2013.01); **H04L 27/0008**  
(2013.01); **H04L 27/3405** (2013.01); **H04L**  
**27/38** (2013.01); **H04L 27/36** (2013.01)

(57) **ABSTRACT**

A coding and modulation apparatus and method are presented. The apparatus (10) comprises an encoder (11) that encodes input data into cell words, and a modulator (12) that modulates said cell words into constellation values of a non-uniform constellation. The modulator (12) is configured to use, based on the total number M of constellation points of the constellation, the signal-to-noise ratio SNR in dB and the channel characteristics, a non-uniform constellation from a group of constellations comprising one or more of predetermined constellations defined by the constellation position vector  $u_1 \dots v$ , wherein  $v = \sqrt{M}/2 - 1$ .

