

US 20240235245A9

(19) United States

(12) Patent Application Publication CHOI

(10) Pub. No.: US 2024/0235245 A9

(48) **Pub. Date: Jul. 11, 2024 CORRECTED PUBLICATION**

(54) THREE-PHASE AND SINGLE-PHASE TWO-WAY CHARGER

(71) Applicant: FOUNDATION FOR RESEARCH
AND BUSINESS, SEOUL
NATIONAL UNIVERSITY OF

SCIENCE AND TECHNOLOGY,

Seoul (KR)

(72) Inventor: Se Wan CHOI, Seoul (KR)

(73) Assignee: FOUNDATION FOR RESEARCH AND BUSINESS, SEOUL

NATIONAL UNIVERSITY OF SCIENCE AND TECHNOLOGY,

Seoul (KR)

(21) Appl. No.: 18/264,065

(22) PCT Filed: Aug. 19, 2021

(86) PCT No.: PCT/KR2021/011039

§ 371 (c)(1),

(2) Date: **Aug. 2, 2023**

Prior Publication Data

(15) Correction of US 2024/0136846 A1 Apr. 25, 2024 See (22) PCT Filed. See (86) PCT No.

(65) US 2024/0136846 A1 Apr. 25, 2024

(30) Foreign Application Priority Data

Feb. 26, 2021	(KR)	10-2021-0026818
Mar. 12, 2021	(KR)	10-2021-0032670

Publication Classification

(51) **Int. Cl. H02J** 7/06 (2006.01)

(57) ABSTRACT

The present technology discloses a three-phase and singlephase two-way charger. According to a specific example of the present invention, a battery charger having a single-stage structure for a combined use of single-phase and three-phase is implemented without an electrolytic capacitor which lowers the reliability and charging efficiency, to enable a compatible use of single-phase and three-phase external power sources, and to improve charging efficiency and the performance in a wide input/output voltage range by a reduced number of switching elements and a soft switching operation of the switching elements and thus improve the reliability and lifetime. A lightweight charger can be realized by integrating, into a core, at least two of an inductor for removing ripples of the battery charger, a primary side and a secondary side of a transformer, and an inductor for removing noise.

