



US 20240213751A1

(19) **United States**

(12) **Patent Application Publication**  
**Rohmer**

(10) **Pub. No.: US 2024/0213751 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **COMPUTER SYSTEM NETWORKING  
DEVICES AND ASSEMBLIES**

*H02G 3/14* (2006.01)

*H02G 3/18* (2006.01)

(71) Applicant: **Pass & Seymour, Inc.**, Syracuse, NY  
(US)

(52) **U.S. Cl.**

CPC ..... *H02G 3/12* (2013.01); *H01R 25/006*  
(2013.01); *H02G 3/14* (2013.01); *H02G 3/18*  
(2013.01)

(72) Inventor: **Richard M. Rohmer**, Memphis, NY  
(US)

(73) Assignee: **Pass & Seymour, Inc.**, Syracuse, NY  
(US)

(57)

**ABSTRACT**

(21) Appl. No.: **18/601,018**

(22) Filed: **Mar. 11, 2024**

**Related U.S. Application Data**

(63) Continuation of application No. 17/125,238, filed on  
Dec. 17, 2020, now Pat. No. 11,979,013.

(60) Provisional application No. 62/948,843, filed on Dec.  
17, 2019.

**Publication Classification**

(51) **Int. Cl.**

*H02G 3/12* (2006.01)

*H01R 25/00* (2006.01)

The present invention is directed to a computer system networking device assembly including a computer system networking device including a computer system networking device module coupled to a power supply circuit, and at least one connection point on the power supply circuit configured to be directly connected via an AC power wire to a mains power supply. The device can include an enclosure housing the device module and power supply circuit; and a subplate or wall plate having a first aperture formed therethrough, wherein the front surface of the enclosure is configured to be positioned through the first aperture formed in a subplate or a wall plate. The subplate or wall plate further can include a second aperture formed therethrough being configured to accommodate at least a portion of an electrical wiring device.

