



US 20240213921A1

(19) **United States**

(12) **Patent Application Publication**
KIM et al.

(10) **Pub. No.: US 2024/0213921 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **SHADE DETECTION AND GLOBAL
MAXIMUM POWER POINT TRACKING
METHOD AND APPARATUS FOR
EFFICIENT PHOTOVOLTAIC POWER
CONVERSION**

Publication Classification

(51) **Int. Cl.**
H02S 50/10 (2006.01)
G05F 1/67 (2006.01)
(52) **U.S. Cl.**
CPC **H02S 50/10** (2014.12); **G05F 1/67**
(2013.01)

(71) Applicant: **POSTECH Research and Business
Development Foundation**, Pohang-si
(KR)

(72) Inventors: **Young Jin KIM**, Pohang-si (KR); **Ji
Hun HA**, Pohang-si (KR); **Ram
Jothikumar PRASANTH**, Pohang-si
(KR)

(73) Assignee: **POSTECH Research and Business
Development Foundation**, Pohang-si
(KR)

(21) Appl. No.: **18/087,769**

(22) Filed: **Dec. 22, 2022**

(30) **Foreign Application Priority Data**

Dec. 21, 2022 (KR) 10-2022-0180336

(57) **ABSTRACT**

Disclosed are a shade detection and global maximum power point tracking method and apparatus for photovoltaic power conversion. The method comprises: setting an array voltage at a first duty and an array current at a second duty among data sheet values of a PV array of a PV module as a reference array voltage and a reference array current, respectively; calculating a MPP resistance of the PV array based thereon; calculating a duty to be applied to a switch of a boost converter of the PV module based on the MPP resistance; obtaining an actual array voltage and an actual array current of the PV array based on the duty; and determining whether a uniform shade case occurs based on the actual array voltage, the actual array current, and actual power.

