US 20230232298A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2023/0232298 A1**

Parichehrehteroujeni et al. (43) **Pub. Date: Jul. 20, 2023**

(54) **RECONFIGURATION PROCEDURE IN A WIRELESS COMMUNICATION NETWORK**

(71) Applicant: **Telefonaktiebolaget LM Ericsson (publ)**, Stockholm (SE)

(72) Inventors: **Ali Parichehrehteroujeni**, Linköping (SE); **Icaro Leonardo Da Silva**, Solna (SE); **Marco Belleschi**, Solna (SE); **Henrik Rydén**, Stockholm (SE); **Luca Lunardi**, Genoa (IT); **Sofia Ek**, Uppsala (SE); **Angelo Centonza**, Torrenueva Costa, Granada (ES)

(21) Appl. No.: **18/010,544**

(22) PCT Filed: **Jun. 15, 2021**

(86) PCT No.: **PCT/SE2021/050580**

§ 371 (c)(1),
(2) Date: **Dec. 15, 2022**

Related U.S. Application Data

(60) Provisional application No. 63/039,276, filed on Jun. 15, 2020.

Publication Classification

(51) **Int. Cl.**
H04W 36/08 (2006.01)
H04W 36/00 (2006.01)

(52) **U.S. Cl.**
CPC ***H04W 36/08*** (2013.01); ***H04W 36/0085*** (2018.08)

(57) **ABSTRACT**

A network node (**1700**) configured to operate as a source network node (**32**) of a reconfiguration procedure transmits signaling to a target network node (**34**) of the reconfiguration procedure. The signaling indicates (i) whether or not the target network node (**34**) is to provide feedback information (**44**) to the source network node (**32**) and/or (ii) which one or more types of feedback information (**44**) the target network node (**34**) is to provide to the source network node (**32**). Based on the received feedback information (**44**), the network node may train a model to predict predicted information, predict the predicted information using the model, and make a decision based on the predicted information.