



US 20240237488A1

(19) **United States**

(12) **Patent Application Publication**
KWON

(10) **Pub. No.: US 2024/0237488 A1**

(43) **Pub. Date: Jul. 11, 2024**

(54) **DISPLAY DEVICE**

(71) Applicant: **LG Display Co., Ltd.**, Seoul (KR)

(72) Inventor: **Ohnam KWON**, Paju-si (KR)

(21) Appl. No.: **18/345,930**

(22) Filed: **Jun. 30, 2023**

(30) **Foreign Application Priority Data**

Jan. 6, 2023 (KR) 10-2023-0002085

Publication Classification

(51) **Int. Cl.**

H10K 59/80 (2006.01)

H10K 59/131 (2006.01)

H10K 59/38 (2006.01)

(52) **U.S. Cl.**

CPC **H10K 59/873** (2023.02); **H10K 59/131**

(2023.02); **H10K 59/38** (2023.02); **H10K**

59/80523 (2023.02); **H10K 59/8722** (2023.02);

H10K 2102/20 (2023.02)

(57)

ABSTRACT

In a display device according to an embodiment of the present disclosure, a second electrode layer which has a higher melting point than that of the first electrode layer has high resistance to laser heat, such that damage thereto may be reduced even when a laser cutting process is performed. Thus, penetration of external defect-causing factors into an organic light-emitting layer may be reduced due to the second electrode layer constituting an outermost layer of the cathode electrode layer.

