

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0213213 A1 Jeng et al.

(43) Pub. Date:

Jun. 27, 2024

(54) EMBEDDED STRESS ABSORBER IN **PACKAGE**

(71) Applicant: Taiwan Semiconductor

Manufacturing Co., Ltd., Hsinchu

(TW)

(72) Inventors: Shin-Puu Jeng, Hsinchu (TW);

Chien-Sheng Chen, Hsinchu (TW); Po-Yao Lin, Zhudong Township (TW);

Po-Chen Lai, Hsinchu (TW); Shu-Shen Yeh, Taoyuan City (TW)

(21) Appl. No.: 18/599,734

(22) Filed: Mar. 8, 2024

Related U.S. Application Data

(60) Continuation of application No. 17/814,788, filed on Jul. 25, 2022, now Pat. No. 11,955,455, which is a division of application No. 17/149,348, filed on Jan. 14, 2021, now Pat. No. 11,532,593.

(60)Provisional application No. 63/085,222, filed on Sep. 30, 2020.

Publication Classification

(51) Int. Cl. H01L 23/00 (2006.01)H01L 23/31 (2006.01)H01L 23/498 (2006.01)H01L 25/00 (2006.01)

(52) U.S. Cl.

CPC H01L 24/81 (2013.01); H01L 23/3121 (2013.01); H01L 23/49822 (2013.01); H01L 24/96 (2013.01); H01L 25/50 (2013.01)

(57)ABSTRACT

A method includes bonding a first package component over a second package component. The second package component includes a plurality of dielectric layers, and a plurality of redistribution lines in the plurality of dielectric layers. The method further includes dispensing a stress absorber on the second package component, curing the stress absorber, and forming an encapsulant on the second package component and the stress absorber.

