



US 20220352889A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2022/0352889 A1****Voss et al.**(43) **Pub. Date: Nov. 3, 2022**(54) **WIDE BANDGAP OPTICAL SWITCH  
CIRCUIT BREAKER**(52) **U.S. Cl.**CPC ..... **H03K 17/78** (2013.01); **H01L 31/0288**  
(2013.01); **H01L 31/09** (2013.01); **H01L**  
**31/03044** (2013.01); **H01L 31/03042**  
(2013.01); **H01L 31/03125** (2013.01)(71) Applicant: **Lawrence Livermore National  
Security, LLC**, Livermore, CA (US)(72) Inventors: **Lars F. Voss**, Livermore, CA (US);  
**Adam M. Conway**, Livermore, CA  
(US)(57) **ABSTRACT**(21) Appl. No.: **17/812,018**(22) Filed: **Jul. 12, 2022****Related U.S. Application Data**(62) Division of application No. 16/430,021, filed on Jun.  
3, 2019.**Publication Classification**(51) **Int. Cl.****H03K 17/78** (2006.01)  
**H01L 31/0288** (2006.01)  
**H01L 31/09** (2006.01)  
**H01L 31/0304** (2006.01)  
**H01L 31/0312** (2006.01)

A high-voltage switch is adapted for use as a medium-voltage direct current circuit breaker, which provides a low-cost, small-footprint device to mitigate system faults. In one example, a method for operating a wideband optical device includes illuminating the wide bandgap optical device with a light within a first range of wavelengths and a first average intensity, allowing a current to propagate therethrough without substantial absorption of the current, illuminating the wide bandgap optical device with light within the first range of wavelengths and a second average intensity that is lower than the first average intensity to allow a sustained current flow through the wide bandgap optical device, and illuminating the wide bandgap optical device with light within a second range of wavelengths to stop or substantially restrict propagation of the current through the wide gap material.

