



US 20230231274A1

(19) **United States**(12) **Patent Application Publication**
HORIUCHI et al.(10) **Pub. No.: US 2023/0231274 A1**(43) **Pub. Date: Jul. 20, 2023**(54) **BATTERY****Publication Classification**(71) Applicant: **MURATA MANUFACTURING CO., LTD.**, Kyoto (JP)(51) **Int. Cl.**
H01M 50/46 (2006.01)
H01M 50/547 (2006.01)
H01M 50/564 (2006.01)(72) Inventors: **Hiroshi HORIUCHI**, Kyoto (JP);
Masayuki IHARA, Kyoto (JP)(52) **U.S. Cl.**
CPC **H01M 50/46** (2021.01); **H01M 50/547**
(2021.01); **H01M 50/564** (2021.01)(21) Appl. No.: **18/127,253**(57) **ABSTRACT**(22) Filed: **Mar. 28, 2023****Related U.S. Application Data**(63) Continuation of application No. PCT/JP2021/
039484, filed on Oct. 26, 2021.(30) **Foreign Application Priority Data**

Nov. 24, 2020 (JP) 2020-194089

Provided is a battery having both high impact resistance and high heat resistance.

Provided is a battery including: a battery element in which a positive electrode and a negative electrode are laminated with a separator interposed therebetween; a fixing member disposed on an end face where a laminated surface of the battery element is exposed; and a tab led out from one end face of the battery element, wherein the separator protrudes from the end face of the battery element, the separator is mutually fused with at least a protruding portion of one of the one end face or another end face opposite to the one end face; and the separator positioned around the tab on the one end face is not mutually fused with the one end face.

