



US 20230231135A1

(19) **United States**(12) **Patent Application Publication**
ZHAO et al.(10) **Pub. No.: US 2023/0231135 A1**(43) **Pub. Date: Jul. 20, 2023**(54) **PROTECTIVE COATINGS FOR LITHIUM
METAL ELECTRODES AND METHODS OF
FORMING THE SAME****H01M 4/38** (2006.01)**H01M 10/0525** (2006.01)(52) **U.S. CL.**CPC **H01M 4/62** (2013.01); **H01M 4/366**
(2013.01); **H01M 4/382** (2013.01); **H01M**
10/0525 (2013.01); **H01M 2004/021** (2013.01)(71) Applicant: **GM GLOBAL TECHNOLOGY
OPERATIONS LLC**, Detroit, MI (US)(72) Inventors: **Yifan ZHAO**, Warren, MI (US);
Xingcheng XIAO, Troy, MI (US);
Shuru CHEN, Troy, MI (US); **Mei**
CAI, Bloomfield Hills, MI (US)

(57)

ABSTRACT(73) Assignee: **GM GLOBAL TECHNOLOGY
OPERATIONS LLC**, Detroit, MI (US)(21) Appl. No.: **17/578,169**(22) Filed: **Jan. 18, 2022****Publication Classification**(51) **Int. Cl.****H01M 4/62** (2006.01)**H01M 4/36** (2006.01)

An electrode includes an electroactive material layer and a protective layer disposed on or adjacent to a surface of the electroactive material layer. The protective layer includes a polymerized cyclic ether and a salt dispersed therewithin. The salt includes a nitrate salt and a phosphate salt. The salt may also include a Lewis acid salt. The protective layer is formed by disposing a solution, including the salt and solvent, on or adjacent to the surface of the electroactive material layer, and polymerizing the solvent. The solvent includes the cyclic ether, and also, one or more organic phosphates.

