US 20240213458A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2024/0213458 A1**

CHUNG et al. (43) **Pub. Date: Jun. 27, 2024**

(54) **ANODE FOR LITHIUM SECONDARY BATTERY AND LITHIUM SECONDARY BATTERY INCLUDING THE SAME**

(71) Applicant: **SK ON CO., LTD.**, Seoul (KR)

(72) Inventors: **Da Bin CHUNG**, Daejeon (KR); **Hyo Mi KIM**, Daejeon (KR); **Hwan Ho JANG**, Daejeon (KR); **Moon Sung KIM**, Daejeon (KR); **Sang Baek RYU**, Daejeon (KR); **Da Hye PARK**, Daejeon (KR); **Sang In BANG**, Daejeon (KR); **Seung Hyun YOOK**, Daejeon (KR); **Jun Hee HAN**, Daejeon (KR)

(21) Appl. No.: **18/540,436**

(22) Filed: **Dec. 14, 2023**

(30) **Foreign Application Priority Data**

Dec. 15, 2022 (KR) 10-2022-0175661

Publication Classification

(51) **Int. Cl.**

H01M 4/36	(2006.01)
H01M 4/133	(2006.01)
H01M 4/134	(2006.01)
H01M 4/38	(2006.01)
H01M 4/587	(2006.01)
H01M 4/62	(2006.01)
H01M 10/052	(2006.01)

(52) **U.S. Cl.**

CPC ***H01M 4/366*** (2013.01); ***H01M 4/133*** (2013.01); ***H01M 4/134*** (2013.01); ***H01M 4/386*** (2013.01); ***H01M 4/587*** (2013.01); ***H01M 4/622*** (2013.01); ***H01M 10/052*** (2013.01); *H01M 2004/027* (2013.01)

(57) **ABSTRACT**

An anode for a lithium secondary battery includes a material layer configured to serve as a current collector, a first anode mixture layer formed on at least one surface of the material layer, and a second anode mixture layer formed on the first anode mixture layer. The first anode mixture layer includes a first silicon-based active material, the second anode mixture layer includes a second silicon-based active material, and a particle volume fraction ratio (R_{PV}) for each layer according to Equation 1 expressed as $R_{PV}=V_{D1}/V_{D2}$ is greater than 1. In Equation 1, V_{D1} is a volume fraction (%) of particles having a particle diameter of 2.5 μm or less in the first silicon-based active material, and V_{D2} is a volume fraction (%) of particles having a particle diameter of 2.5 μm or less in the second silicon-based active material.