

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2023/0231133 A1 NAGAMITSU et al.

(43) **Pub. Date:**

Jul. 20, 2023

(54) ELECTROCHEMICAL DEVICE

(71) Applicant: Panasonic Intellectual Property Management Co., Ltd., Osaka (JP)

(72) Inventors: **KENICHI NAGAMITSU**, Kyoto (JP); NOBUHIRO SHIMAMURA, Osaka

(JP)

17/998,946 (21) Appl. No.:

PCT Filed: May 18, 2021

(86) PCT No.: PCT/JP2021/018830

§ 371 (c)(1),

(2) Date: Nov. 16, 2022

(30)Foreign Application Priority Data

(JP) 2020-100392

Publication Classification

(51) **Int. Cl.** H01M 4/587 (2006.01)H01M 10/0525 (2006.01)H01M 10/0562 (2006.01)H01M 4/133 (2006.01)H01G 11/42 (2006.01) H01G 11/66 (2006.01)(2006.01)H01G 11/58

(52) U.S. Cl.

CPC H01M 4/587 (2013.01); H01M 10/0525 (2013.01); H01M 10/0562 (2013.01); H01M 4/133 (2013.01); H01G 11/42 (2013.01); H01G 11/66 (2013.01); H01G 11/58 (2013.01); H01M 2300/008 (2013.01); H01M 2004/021 (2013.01)

(57)**ABSTRACT**

An electrochemical device includes a positive electrode, a negative electrode, and an electrolyte having lithium ion conductivity. The positive electrode includes a positive current collector and a positive electrode mixture layer supported on the positive current collector. The positive electrode mixture layer contains a positive electrode active material reversibly doped with an anion. The negative electrode includes a negative current collector and a negative electrode mixture layer supported on the negative current collector. The negative electrode mixture layer contains a negative electrode active material reversibly doped with lithium ions. The negative electrode active material contains non-graphitizable carbon. A ratio Mp/Mn of a mass Mp of the positive electrode active material supported on a unit area of the positive electrode to a mass Mn of the negative electrode active material supported on a unit area of the negative electrode is in a range from 1.1 to 2.5, inclusive.

