US 20240213791A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2024/0213791 A1**

MURAKAMI (43) **Pub. Date: Jun. 27, 2024**

(54) **REDUNDANT POWER SUPPLY CONTROL DEVICE AND CONTROL METHOD**

(71) Applicant: **TOYOTA JIDOSHA KABUSHIKI KAISHA**, Toyota-shi (JP)

(72) Inventor: **Makoto MURAKAMI**, Toyota-shi (JP)

(73) Assignee: **TOYOTA JIDOSHA KABUSHIKI KAISHA**, Toyota-shi (JP)

(21) Appl. No.: **18/490,249**

(22) Filed: **Oct. 19, 2023**

(30) **Foreign Application Priority Data**

Dec. 27, 2022 (JP) 2022-210211

Publication Classification

(51) **Int. Cl.**
H02J 7/00 (2006.01)

(52) **U.S. Cl.**
CPC ***H02J 7/0068*** (2013.01); ***H02J 7/0047*** (2013.01)

(57) **ABSTRACT**

A redundant power supply control device controls a sub-battery capable of backing up the main battery. The control device includes an acquisition unit, an estimation unit, and a determination unit. The acquisition unit obtains a voltage value and a current value of the sub-battery. The estimation unit estimates the storage rate of the sub-battery by current integration. The determination unit determines whether the sub-battery can be backed up. The determination unit calculates a first resistance value that is an internal resistance value of the sub-battery estimated based on the measured voltage value and the measured current value, and calculates a second resistance value that is an internal resistance value of the sub- battery estimated based on the estimated voltage value and the measured current value. The determination unit determines whether the sub-battery can be backed up based on the larger one of the first resistance value and the second resistance value.